

POWERSTAR® 1100 DENSIFYING TREATMENT

Clear, odorless, neutral pH solution that penetrates concrete to enhance dyes and create a harder, more durable surface. Will not gel, eliminating any problem if allowed to dry on the substrate.

FEATURES

- *Clear and odorless*
- *No rinsing or disposal*
- *Does not gel*
- *Reduces tire marks*



RECOMMENDED APPLICATIONS

For concrete, stucco, and terrazzo.

PRODUCT DATA

Appearance:	Clear, colorless liquid
Fragrance:	None added
pH:	6.5 ± 0.5 ASTM E70-97
Density:	8.68 lb per gal @ 68°F 1.04 kg per liter @ 20°C
Flash Point:	None
Freeze/Thaw:	Do not freeze
Shelf Life:	1 year

PRECAUTIONS

Keep out of reach of children. Keep container sealed when not in use. Avoid freezing. If frozen, allow to return to room temperature slowly; mix thoroughly before using.

ORDERING INFORMATION

Product #419GL5:	2 x 2.5 gallons per case (2 x 9.5 liters)
Product #419DR5:	55 gallons

DIRECTIONS FOR USE:

1. Apply with low-pressure sprayer or automatic scrubber. Can be moved with a brush, broom, or automatic scrubber to ensure uniform coverage.
2. Keep surface wet with PowerStar 1100 Densifying Treatment for a minimum of 60 minutes.
3. Allow floor to air dry. Do not remove the spent material from the floor.
4. After PowerStar 1100 Densifying Treatment has dried, any un-reacted material can be removed with a broom.

NOTE: PowerStar 1100 Densifying Treatment is a RTU product designed to be used undiluted.

USE PRECAUTIONS

Allow to dry 1 to 2 hours prior to exposure to traffic.


POWERSTAR 1100 DENSIFYING TREATMENT

LAST REVISION DATE: 05/21/08
MANUFACTURER: Amano Pioneer Eclipse® Corp.
 Sparta, NC 28675 Phone: 1-336-372-8080.
FOR CHEMICAL EMERGENCY: Spill, Leak, Fire,
 Exposure or Accident **CALL CHEMTREC - Day
 or Night 1-800-424-9300** Toll Free in the
 Continental US **483-7616** in DISTRICT OF
 COLUMBIA. For calls originating outside the US:
 Call Collect **1-202-483-7616** Washington, DC.

SECTION I: GENERAL INFORMATION

PRODUCT NAME: PowerStar® 1100 Densifying
 Treatment
PRODUCT #: 419
DESCRIPTION: Clear, colorless liquid
PRECAUTIONS: Possible skin and eye irritant.
 Keep container sealed when not in use. Keep out
 of reach of children.
FLAMMABILITY: 0
REACTIVITY: 0
HEALTH: 1
NFPA HAZARD RATINGS

4-EXTREME	3-HIGH	2-MODERATE
1-SLIGHT	0-INSIGNIFICANT	



SECTION II: HAZARDOUS INGREDIENTS

INGREDIENT: Silica, amorphous
CAS#: 7631-86-9
%: 10-30
OSHA PEL: 6 ppm (TWA)
ACGIH TLV: 6 ppm (TWA)
LD₅₀ SPECIES & ROUTE: >5000 mg/kg rat, oral

N/E = Not Established, N/L = Not Listed,
 N/A = Not Applicable

SECTION III: PHYSICAL/CHEMICAL DATA

APPEARANCE: Clear, colorless
pH: 6.5 ± 0.5
BOILING POINT: 100°C / 212°F
EVAPORATION RATE: Less than water
FREEZING POINT: 0°C / 32°F
VAPOR DENSITY: Greater than air
VAPOR PRESSURE: Less than water
DENSITY: 8.68 lb per gal @ 68°F
 1.04 kg per liter @ 20°C
SOLUBILITY IN WATER: Miscible

SECTION IV: FIRE AND EXPLOSION DATA

FLASH POINT: Non-combustible
EXPLOSIVE LIMITS:
 LOWER: N/A UPPER: N/A
EXTINGUISHING MEDIA: N/A
SPECIAL FIRE FIGHTING PROCEDURES: None
HAZARDOUS COMBUSTIBLE PRODUCTS: Oxides
 of carbon
UNUSUAL FIRE AND EXPLOSION HAZARDS:
 Materials can splatter above 100°C / 212°F.
 Polymer can burn.

SECTION V: REACTIVITY DATA

STABILITY: Stable
HAZARDOUS POLYMERIZATION: Will not occur.
INCOMPATIBILITY (MATERIALS TO AVOID):
 Strong acids and bases.
HAZARDOUS DECOMPOSITION PRODUCTS: N/A
REACTIVITY CONDITIONS: None

SECTION VI: HEALTH HAZARD DATA

EYES: Slightly irritating to eyes. For eye contact,
 flush with a large amount of water for at least
 15 minutes. See a physician if irritation persists.
SKIN: Irritating to skin upon repeated or
 prolonged contact. For skin contact, wash
 affected areas with soap and water.
INHALATION: Vapor or mist can cause irritation
 of the eyes, nose, throat and lungs. For
 overexposure, move subject to fresh air.
INGESTION: Irritation to mouth, esophagus
 and stomach. If ingested, drink two glasses of
 water and do not induce vomiting.
 Seek medical attention.
**CHRONIC EFFECTS AND MEDICAL CONDITIONS
 AGGRAVATED BY OVEREXPOSURE:** Prolonged or
 repeated contact can cause drying, defatting and
 dermatitis to skin.
CARCINOGEN: Non-carcinogenic
REPRODUCTIVE EFFECTS: N/E
TERATOGENICITY: N/E
MUTAGENICITY: N/E
THRESHOLD LIMIT VALUE: See Section II.

SECTION VII: SPILL, LEAK & DISPOSAL PROCEDURES

SMALL SPILLS: Absorb spill with inert material
 (e.g. sand, earth) and dispose of as waste
 material in accordance with local, state and
 federal regulations.
LARGE SPILLS: Keep spectators away. Floors
 may be slippery; use care to avoid falling. Dike
 and contain spill with inert material (e.g. sand,
 earth). Transfer liquid to containers for recovery
 or disposal and solid diking material to separate
 containers for disposal. Keep spills and cleaning
 runoff out of sewers and open bodies of water.
WASTE DISPOSAL: Dispose of as waste
 material in accordance with local, state, and
 federal regulations.

SECTION VIII: SPECIAL PROTECTION

PERSONAL PROTECTIVE EQUIPMENT (PPE)
EYES: None required under normal conditions of
 use. Safety glasses recommended.
SKIN: If prolonged or repeated contact is
 possible, chemical-resistant clothing (e.g., rubber
 gloves) is recommended.
RESPIRATORY: No respiratory protection is
 required if ventilation is adequate.
ENGINEERING CONTROLS: Good general room
 ventilation is expected to be adequate. Local
 exhaust ventilation (e.g., fans) may be necessary
 when general ventilation does not keep airborne
 concentrations below any exposure limits.

SECTION IX: SPECIAL PRECAUTIONS

HANDLING AND STORAGE:
 Storage temperature (MAX. 60°C / 140°F)
 (MIN. 1°C / 34°F)
OTHER PRECAUTIONS: Keep from freezing;
 product may coagulate.

SECTION X: ADDITIONAL INFORMATION

Neither this data sheet nor any statement
 contained herein grants or extends any license,
 expressed or implied, in connection with patents
 issued or pending which may be the property
 of the manufacturer or others. The information
 in this data sheet has been assembled by the
 manufacturer based on its own studies and
 the work of others. The manufacturer makes
 no warranties, expressed or implied, as to the
 accuracy, completeness or adequacy of the
 information contained herein. The manufacturer
 shall not be liable (regardless of fault) or the
 vendee, the vendee's employees or anyone for
 any direct, special or consequential damages
 arising out of or in connection with the
 accuracy, completeness, adequacy or
 furnishing of such information.

This MSDS has been provided to you in accordance
 with the OSHA HAZARD COMMUNICATION STANDARD
 (29CFR1910.1200).

***IMPORTANT SAFETY INFORMATION
 DO NOT DISCARD***
 PLEASE ROUTE TO COMPANY SAFETY OFFICER

