

revolution®

RIDE-ON UHS PROPANE BURNISHER

RXL33DLX & RXL40DLX

PRODUCT DATA



FEATURES

- Propane power offers unlimited run-time with no down time for recharging batteries
- Easy pad changing with infinitely adjustable pad pressure
- State-of-the-art Emissions Control System and safety shut down feature
- Advanced LED instrument panel with engine diagnostic trouble-shooting codes
- Optimum burnishing with true 360 degree pad contact
- Dust collection system with dust box, washable filter, and floating steel skirt
- Superior maneuverability with true-zero turning radius
- 33.5 lb (15 kg) propane cylinder
- Lowest noise in the industry
- Electric clutch
- CGA listed, CARB/EPA certified, CE approved



SPECIFICATIONS

Performance:	33 in – 51,000 ft ² /hr (± 4750 m ² /hr) 40 in – 62,000 ft ² /hr (± 5760 m ² /hr)	Noise Level:	85 dBA
Pad Pressure:	15 - 75 psi	Vibration Level:	Less than 2.5 m/s ²
Pad Speed:	2050 RPM	Engine:	Kawasaki 675cc, Water-cooled
Pad Size:	33 in – 2 x 17 in (2 x 43 cm) 40 in – 2 x 21 in (2 x 53 cm)	Engine Speed:	1600 - 3600 RPM
Start:	12V Battery	Fuel System:	Electronic Fuel Injection
Forward Speed:	4.5 mph (7 km/h)	Length x Width x Height:	33 in – 65 in x 35.5 in x 46.5 in (165 cm x 90 cm x 135 cm) 40 in – 69 in x 44 in x 53 in (175 cm x 112 cm x 135 cm)
Reverse Speed:	3.0 mph (5 km/h)	Weight:	33 in – 765 lb (347 kg) 40 in – 780 lb (354 kg)
Turning Radius:	Zero		
Steering:	Self-contained Hydraulic Rear-wheel		
Wheel Drive:	Self-contained Hydrostatic Pump with Single Rear-wheel Drive Hydraulic Motor		